

## Datasheet Well Tractor® 218 NG

The Well Tractor® NG is the latest development in deployment tools from Welltec®. Building on twenty years of tractor experience, Welltec® has incorporated that knowledge into improved performance. Faster, stronger and more compact than the standard versions of the Well Tractor®, the NG tools enable operators to extend the reach of traditional e-line deployment into highly deviated and horizontal wells even more efficiently.

Applications	Features	Benefits
• Clean-out solutions	• Passive fail-safe system	• Prevents stuck tools
• Perforating	• Modular	• High speed vs high force
• Milling / Mechanical solutions	• Surface readout compatible	• Maximum efficiency
• Fluid sampling	• Logging while tractoring	• Optimal data acquisition
• Fishing / Pipe recovery	• Universal through wiring	• OH or CH application
• Seismic measurement	• NACE compliant	• Operates on any e-line via DC
• SAGD ranging		
• Depth determination		

Specifications*	Imperial	Metric
• Length	• 16 ft	• 4.9 m
• Running OD nominal	• 2 1/8"	• 54 mm
• Weight in air	• 175 lbs	• 79 Kg
• OH / Completion ID range	• 2.2" – 9.1"	• 56 mm – 231 mm
• Optimized force configuration	• 900 lbs @ 2,100 ft/hr	• 408 Kg @ 640 m/hr
• Optimized speed configuration	• 450 lbs @ 4,100 ft/hr	• 204 Kg @ 1,250 m/hr
• Maximum well pressure	• 20,000 psi	• 137 MPa (1,379 bar)
• Maximum well temperature	• 302 F	• 150 °C
• Tensile strength	• 36,000 lbs	• 16,300 Kg
• Compressive strength	• 30,000 lbs	• 13,600 Kg

\* Dependent upon configuration

