

Datasheet Well Cleaner® 218 Wishbone honer

The Well Cleaner® with rotating heads is designed specifically to remove deposits left on the walls or completion components in the well. Over time, these often lead to decreased production or malfunctioning hardware. The Well Cleaner's different rotating heads remove these deposits to restore full functionality and production.

Applications	Features	Benefits
• Removal of deposits or debris	• Passive fail-safe system	• No additional fluids required
• Cleaning SSSV seats	• Modular	• Removes a wide range of debris
• Clearing obstructions	• Surface read-out compatible	• Large range of ID's accessible
• Accessing isolation valves	• Variable heads based on objective	• Accurate depth control
	• Universal	• Operates on any e-line via DC
	• NACE compliant	

Specifications*	Imperial	Metric
• Length	• 13 ft	• 4.0 m
• Running OD nominal	• 2 1/8"	• 54 mm
• Weight in air	• 75 lbs	• 34 kg
• Completion ID range	• 2.25" – 7"	• 57 mm – 178 mm
• Brush diameter	• 2.125 – 3.395"	• 54 mm – 86 mm
• Maximum well pressure	• 25,000 psi	• 1,720 bar
• Maximum well temperature	• 302 F	• 150 °C
• Tensile strength	• 36,000 lbs	• 16,300 Kg
• Compressive strength	• 30,000 lbs	• 13,600 Kg

* Dependent upon configuration

