

DATA SHEET WELL TRACTOR® 212 NG

The Well Tractor® NG is the latest development in deployment tools from Welltec®. Building on twenty years of tractor experience, Welltec® has incorporated that knowledge into improved performance. Faster, stronger and more compact than the standard versions of the Well Tractor®, the NG tools enable operators to extend the reach of traditional e-line deployment into highly deviated and horizontal wells even more efficiently.

APPLICATIONS

- Clean-out solutions
- Perforating
- Milling solution
- Fluid sampling
- Mechanical solutions
- Pipe recovery
- Fishing
- SAGD ranging
- Depth determination
- Seismic measurement
- Any e-line service

FEATURES

- Passive fail-safe system
- Modular
- Surface read-out compatible
- Logging while tracting
- Universal through wiring
- NACE compliant

BENEFITS

- Prevents stuck tools
- High speed vs high force
- Maximum efficiency
- Optimal data acquisition
- OH or CH application
- Operates on any e-line via DC



SPECIFICATIONS*	IMPERIAL	METRIC
Length	18.4 ft	5.6 m
Running OD nominal	2 1/2"	64 mm
Weight in air	205 lbs	93 Kg
OH / Completion ID range	2.6" – 10.1"	66 mm – 257 mm
Optimized force configuration	2200 lbs @ 2000 ft/hr	1000 Kg @ 610 m/hr
Optimized speed configuration	1150 lbs @ 4300 ft/hr	520 Kg @ 1310 m/hr
Maximum well pressure	25,000 psi	172 MPa (1,720 bar)
Maximum well temperature	302 F	150 °C
Tensile strength	37,000 lbs	16,800 Kg
Compressive strength	44,000 lbs	20,000 Kg

*Dependant upon configuration