

DATA SHEET WELL CLEANER® 218

POWER SUCTION TOOL - STANDARD

The Well Cleaner® Power Suction Tool (PST) is the ideal choice for removal of loose debris in the well. Using high-rate fluid circulation, the Well Cleaner® PST agitates the debris and then captures it in bailer sections within the tool. It can be run independently in vertical wells or combined with the Well Tractor® for clean-outs in highly deviated or horizontal wells.

APPLICATIONS

- Removing sand and debris
- Cleaning SSSV seats
- Clearing obstructions
- Accessing isolation valves

FEATURES

- Powerful suction
- Variable nozzle designs
- Configurable
- Integrated bailers in various sizes
- Modular
- Universal
- NACE compliant

BENEFITS

- No additional fluids required
- Measureable recovery
- Removes wide range of debris
- Recovers the debris from the well
- High recovery rate
- Accurate depth control
- Operates on any e-line via DC



SPECIFICATIONS*	IMPERIAL	METRIC
Length	26.6 ft	8.1 m
Running OD nominal	2 1/8"	54 mm
Weight in air	172 lbs	78 Kg
Completion ID range	2.2" – 8.2"	56 mm – 208 mm
Available bailer sizes	2.125" – 2.5"	54 mm – 64 mm
Volume / three bailer	1.9 – 2.97 gals	7.2 – 11.2 l
Maximum well pressure	20,000 psi	1,400 bar
Maximum well temperature	302 F	150 °C
Tensile strength	24,000 lbs	10,900 Kg
Compressive strength	50,000 lbs	22,700 Kg

*Dependent upon configuration