

DATA SHEET WELL CLEANER® 318

POWER SUCTION TOOL - STANDARD

The Well Cleaner® Power Suction Tool (PST) is the ideal choice for removal of loose debris in the well. Using high-rate fluid circulation, the Well Cleaner® PST agitates the debris and then captures it in bailer sections within the tool. It can be run independently in vertical wells or combined with the Well Tractor® for clean-outs in highly deviated or horizontal wells.

APPLICATIONS

- Removing sand and debris
- Cleaning SSSV seats
- Clearing obstructions
- Accessing isolation valves

FEATURES

- Powerful suction
- Variable nozzle designs
- Configurable
- Integrated bailers in various sizes
- Modular
- Universal
- NACE compliant

BENEFITS

- No additional fluids required
- Measureable recovery
- Removes wide range of debris
- Recovers the debris from the well
- High recovery rate
- Accurate depth control
- Operates on any e-line via DC



SPECIFICATIONS*	IMPERIAL	METRIC
Length	21.6 - 24 ft	6.6 m - 7.3 m
Running OD nominal	3 1/8"	80 mm
Weight in air	309 - 375 lbs	140 Kg – 170 Kg
Completion ID range	3.4" – 12.6"	86 mm – 320 mm
Available bailer sizes	3.125" – 4"	80 mm – 101 mm
Volume / three bailer	5.2 – 8.21 gals	20 – 31 l
Maximum well pressure	25,000 psi	1,720 bar
Maximum well temperature	302 F	150 °C
Tensile strength	38,000 lbs	17,200 Kg
Compressive strength	50,000 lbs	22,700 Kg

*Dependent upon configuration