

DATA SHEET WELL TRACTOR® 318

STANDARD / XR

The Well Tractor® was regarded as a revolution in the industry when it was introduced to the market in the 1990's. It enables operators to extend the reach of traditional e-line deployment into highly deviated and horizontal wells, making it one of the most cost-effective and successful applications for deployment in well interventions.

APPLICATIONS

- Clean-out solutions
- Perforating
- Milling solutions
- Fluid sampling
- Mechanical solutions
- Pipe recovery
- Fishing
- SAGD ranging
- Depth determination
- Seismic measurements
- Any e-line service

FEATURES

- Passive fail-safe system
- Modular
- Surface read-out
- Logging while tractoring
- Wide range of sizes
- Universal through wiring
- NACE compliant

BENEFITS

- Prevents stuck tools
- High speed vs high force
- Configurable
- Maximum efficiency
- Optimal data acquisition
- OH or CH applications
- Large range of ID's accessible
- Operates on any e-line via DC



SPECIFICATIONS*	IMPERIAL	METRIC
Length	19 ft	5.8 m
Running OD nominal	3 1/8"	80 mm
Weight in air	400 lbs	181 Kg
OH / Completion ID range	3.4" – 12.6"	86 mm – 320 mm
Optimized force configuration	2,100 lbs @ 1,200 ft/hr	950 Kg @ 370 m/hr
Optimized speed configuration	800 lbs @ 5,000 ft/hr	360 Kg @ 1,500 m/hr
Maximum well pressure	25,000 psi	172 MPa (1,720 Bar)
Maximum well temperature	302 F	150 °C
Tensile strength	42,000 lbs	19,000 Kg
Compressive strength	50,000 lbs	22,700 Kg

*Dependent upon configuration