

DATA SHEET WELL TRACTOR® 218

STANDARD / XR – HIGH TEMP

The Well Tractor® was regarded as a revolution in the industry when it was introduced to the market in the 1990's. It enables operators to extend the reach of traditional e-line deployment into highly deviated and horizontal wells, making it one of the most cost-effective and successful applications for deployment in well interventions. This AC version is capable of operating in environments up to 392 deg F.

APPLICATIONS

- Clean-out solutions
- Perforating
- Milling solutions
- Fluid sampling
- Mechanical solutions
- Pipe recovery
- Fishing
- SAGD ranging
- Depth determination
- Seismic measurements
- Any e-line service

FEATURES

- Passive fail-safe system
- Modular
- Surface read-out
- Logging while tractoring
- Wide range of sizes
- Universal through wiring
- NACE compliant

BENEFITS

- Prevents stuck tools
- High speed vs high force
- Configurable
- Maximum efficiency
- Optimal data acquisition
- OH or CH applications
- Large range of ID's accessible
- Operates on e-line via AC



SPECIFICATIONS*	IMPERIAL	METRIC
Length	16 ft	4.9 m
Running OD nominal	2 1/8"	54 mm
Weight in air	175 lbs	79 Kg
OH / Completion ID range	2.2" – 9.2"	56 mm – 234 mm
Optimized force configuration	800 lbs @ 1,200 ft/hr	360 Kg @ 370 m/hr
Optimized speed configuration	400 lbs @ 3,600 ft/hr	180 Kg @ 1,100 m/hr
Maximum well pressure	25,000 psi	172 MPa (1,720 Bar)
Maximum well temperature	392 F	200 °C
Tensile strength	36,000 lbs	16,300 Kg
Compressive strength	30,000 lbs	13,600 Kg

*Dependent upon configuration